aspire

RHEA X Kit User Manual

Sturdy, Durable, Lightweight.

EN

SAFETY INFORMATION
For a safe and effective use of this product and its accessories, we advise you to read the following instructions in full, and to strictly observe the operating procedures indicated in this manual. Aspire cannot be held responsible for any damage of the individual product's accessories after reading, store it in a safe place for future reference. Incorrect charger when fully charged can cause damage to the battery and even a risk of fire or damage. The manufacturer assumes no responsibility for any damage caused by mishandling that is beyond normal usage defined in this manual.

This product is intended for adult smokers. This product is not recommended for non-smokers, young people under the legal age, pregnant or breast feeding women and those experiencing general ill-health.

Keep the product and its accessories out of reach of children and animals at all times!

COMPONENTS OF THE PRODUCT
Do not discard this product and its components such as the battery, the USB cable, and the tank/pod unit have been specifically made for this product. We recommend the exclusive use of components and accessories indicated. Use of components and / or accessories not specifically produced for this product may result in damage to the product and void the product and / or the cancellation of the warranty.

WARNING BEFORE USE
Do not use if you notice any damage to the product can cause immediate damage to the internal resistance and the consequent cancellation of the warranty.

GENERAL WARNINGS AND LIMITATIONS OF USE
Do not bring your vape device into contact with water or other e-liquid. Avoid exposing the device to too low or too high temperatures (0°C / 32°F or 60°C / 140°F) and avoid mechanical or excessively damp environments. Keep the product and its accessories away from heat sources. Use only the battery charger provided with the device. Do not use a battery charger with battery technology. Carefully read the composition of the e-liquid before use, and do not use the product if you are allergic to any of the components of the e-liquid. Do not use the product if you suffer from respiratory and / or cardiovascular system disorders. Do not use the product during pregnancy or lactation.

If you notice any unusual behavior of the device (such as heating without button activation), turn off the device immediately and remove the battery. Contact Aspire Customer Service.

WARNINGS FOR REPLACEABLE BATTERIES:
• Only use batteries recommended by Aspire.
• Do not use damaged batteries or batteries with a torn or damaged wrapper.
• Do not disassemble or modify batteries at a dedicated battery collection point.
• Replaceable batteries are not included in the package.
• Use of non-certified batteries may lead to a malfunction or damage to the product and to the cancellation of the warranty.

Contents:
1* RHEA X Mesh (18650 Battery Not Included)
1* Hexagon Tank
1* 8P Mesh Coil 0.5Ω (Preinstalled)
1* Glass Tube Tank
1* Spare Glass Tube
1* Tuberti Cable
1* Drip Tip Adapter
1* Orange Ring

Components View:

Tank Features:
810 Adjustable drip tip
Top fill
Top adjustable airflow
Leak-resistant design
Capacity: 5.5ml / 0.18oz (Glass) 4.5ml (Pyrex)
Dimensions (including drip tip): 22.5*52.1mm

Mod Specifications:
510 connector
External single 18650 battery
(Please use high rate discharge battery)
Output voltage: 3.0-4.2V (Adjustable) TC:OFF
Output wattage range: 5-70W
Output voltage range: 0.5-8V
Adjustable temperature range: 200-600°F/ 100-315°C
Supported resistance: 0.08-3.0Ω
Puff detection: 8s cut off
Cold: 777 coil for cooler vaping
Charging: Type-C, 2A
Mod dimensions: 27.5*52*46 mm

Coil Installation:



Tank Filling:



Parameters Setting:
Step 1: Enter the main interface, the screen will display "WATT/VOLTAGE/OHM/TEMP CONTROL/BYPASS/PUFFS/TIME/PREHEAT".
Step 2: Long press mode button on the main interface to enter the menu adjustment.
Short press mode button to switch the menu: "WATT/VOLTAGE/OHM/TEMP CONTROL/BYPASS/PUFFS/TIME/PREHEAT".
• Press "+" / "-" button to switch the mode between WATT, VOLTAGE, BYPASS, CPS, and TCW2/TCR/TCNI.
• Press "+" / "-" button to set and save the parameters and keep the settings.

Mode	Adjustment range	Operation and value setting
WATT	1-160W (Default: 5W)	Press "+" / "-" button to enter adjustment mode, long press "+" / "-" button for quick adjustment.
VOLTAGE	0.5-8V (Default: 4.85V)	Press "+" / "-" button to enter adjustment mode, long press "+" / "-" button for quick adjustment.
BYPASS	Maximum voltage 8.5V, maximum wattage 160W	Press "+" / "-" button to enter adjustment mode, long press "+" / "-" button for quick adjustment.
CPS	1-160W (Default: 100W)	Press "+" / "-" button to enter adjustment mode, long press "+" / "-" button for quick adjustment.
TC	200-600°F (Default: 350°F)	Press "+" / "-" button to enter adjustment mode, long press "+" / "-" button for quick adjustment.

Note:
1. The device will display "NEW ATOMIZER" with a low TC mode. Please activate the atomizer with a low wattage (10-15W) before the puffs will return to the default value of 350°F and will fully

update present vaping puffs if you vape press "+" button, the puffs will display the puff value of last time.

Safety Features:

Low Voltage Protection	The screen will display "LOW BATT"
Short Circuit Protection	The screen will display "ATOMIZER SHORT"
Low Voltage Protection	The screen will display "LOW BATT"
Overcharge Protection	The device will stop charging
Over Heat Protection	The screen will display "OVER HEAT"
Battery Reverse Protection	The device will stop working

Battery Installation:

Battery Installation:

Charging current	2A
Charging voltage	5V
When the Type-C cable is plugging	The screen will display a glowing battery icon
Fully charged	The screen will be on for 10s and the battery icon will be solid
Battery Level Display	4.2V~3.7V=100%~75% 3.7V~3.6V=75%~50% 3.6V~3.5V=50%~25% 3.5V~3.2V=25%~0% Battery level will display in 4 levels
The charging time	The device will stop charging and the screen will display "CHARGE FULL"

IMPORTANT INFORMATION ABOUT USING NICOTINE CONTAINING E-LIQUIDS

Before using nicotine containing e-liquid the user should read the following information carefully.

NICOTINE CONTAINING E-LIQUID:
Do not use if you are allergic to nicotine or any of the other ingredients contained within the e-liquid (see manufacturer's label for full details).

WARNINGS AND PRECAUTIONS:
Nicotine containing e-liquid are not recommended for:
• Non-smokers
• Young people under the legal age.
• Pregnant or breast feeding women as nicotine is known to cause harm to the developing foetus or breast milk.
• Those experiencing general ill health, such as heart disease, circulatory problems, diabetes, or those taking medication for high blood disease or difficulty breathing due to bronchitis, emphysema or asthma.
• Those who have had a cerebrovascular thrombi (glots) or have a history of ulcers or a tumor of the adrenal gland that can affect high blood pressure).
• Those with severe diabetes, as nicotine may affect your blood sugar levels.
• Those taking the following medication:
• Insulin (as nicotine may affect insulin absorption)
• Ibuprofen (as heart pain symptoms)
• Clonazepine (to treat schizophrenia)

POSSIBLE SIDE EFFECTS:
If any initially non-touch nicotine or use the product too much can lead to nicotine poisoning and in rare cases of the extra products can show traces of nicotine.

NOTA DE SEGURIDAD
Para evitar errores de encendido, asegúrese siempre de bloquear o apagar el dispositivo cuando no esté en uso. Mantenga el dispositivo fuera del alcance de los niños y las mascotas.

ADVERTENCIAS PARA BATERÍAS REEMPLAZABLES:
• No utilice pilas no recomendadas por Aspire.
• No utilice pilas o baterías dañadas con un envoltorio roto o dañado.
• No desmonte ni modifique las pilas en un punto de recogida/eliminación dedicado.
• Las pilas reemplazables no están incluidas en el paquete.
• El uso de pilas no certificadas puede dar lugar a una mal funcionamiento o daños en el producto y a la cancelación de la garantía.

ADVERTENCIAS ANTE EL USO DE LA UNIDAD
Los productos con una batería interna vienen cargados de fábrica completamente. No la recargue hasta que el indicador LED muestre que está llena. Utilice solo el cable de carga USB suministrado con el producto. Si no se carga, vea si el dispositivo puede causar daños inmediatos a la resistencia interna y la garantía quedará cancelada.

ADVERTENCIAS GENERALES Y LIMITACIONES DE USO
No ponga en contacto su dispositivo de vapeo con agua u otro líquido electrónico. Evite exponer el dispositivo a temperaturas demasiado bajas o demasiado altas (-10ºC / 32ºC). Evite ambientes mecánicos o excesivamente húmedos.
Mantenga el producto y sus accesorios alejados de fuentes de calor. Utilice únicamente el cargador de batería suministrado con el dispositivo. No utilice un cargador de batería con tecnología. Lea atentamente la composición del e-líquido antes de usar, y no utilice el producto si es alérgico a alguno de los componentes del e-líquido. No utilice el producto si sufre trastornos respiratorios y/o del sistema cardiovascular. No utilice el producto durante el embarazo o la lactancia.
Si observa algún comportamiento inusual del dispositivo (como calentamiento sin activación del botón), apague el dispositivo inmediatamente y retire la batería. Póngase en contacto con el servicio de atención al cliente de Aspire.

ADVERTENCIAS PARA BATERÍAS RECARGABLES:
• Utilice solo baterías recomendadas por Aspire.
• No utilice baterías dañadas con un envoltorio roto o dañado.
• No desmonte ni modifique las baterías en un punto de recogida dedicado.
• Las baterías recargables no se incluyen en el paquete.
• El uso de baterías no certificadas puede provocar un mal funcionamiento o daños en el producto y la cancelación de la garantía.

Especificaciones del mod:
Conector 510
Batería externa de 18650
(Por favor utilice una batería de alta velocidad de descarga.)
Modos de salida: WATT / VOLTAGE / BYPASS / TC / CPS
Rango de voltaje de salida: 3.0-4.2V
Rango de voltaje de salida: 0.5-8 V
Rango de temperatura ajustable: 200-600ºF/ 100-315ºC
Resistencia soportada: 0.08-3.0Ω
Tiempo de calada continua: 10s
Cold: 777 coil for cooler vaping
Puerto de carga Tipo C
Dimensiones del mod: 27.5 * 52 * 46 mm

Instalación de la resistencia:



Llenado del tanque:

Características del tanque:
Boquilla 810 ajustable
Capacidad del tanque: 5.5 ml
Relleno superior
Flujo de aire ajustable superior
Resistencia antifugas
Dimensiones (incluida la boquilla): 22.5*52.1mm

Características del tanque:
Boquilla 810 ajustable
Capacidad del tanque: 4.5 ml
Relleno superior
Flujo de aire ajustable superior
Resistencia antifugas
Dimensiones (incluida la boquilla): 22.5*52.1mm

Contenido:
1* Mod RHEA X (Batería 18650 no incluida)
1* Tanque hexagonal
1* Resistencia de malla 8P Pre de 0.5Ω
1* Tubo de cristal de repuesto
1* Cable Tuberti
1* Adaptador de boquilla
1* Anillo de boquilla naranja

Vista de componentes:



Configuración de parámetros:
Paso 1: Entra la pantalla principal, la pantalla mostrará "WATT/VOLT/OHM/TEMP CONTROL/BYPASS/PUFFS/TIME/PREHEAT".
Paso 2: Presione el botón de modo durante mucho tiempo en la interfaz principal para entrar al ajuste del menú.
Presione el botón de modo para cambiar el modo: "WATT/VOLT/OHM/TEMP CONTROL/BYPASS/PUFFS/TIME/PREHEAT".
• Presione el botón "+" / "-" para cambiar el modo entre WATT, VOLT, BYPASS, CPS, TCW2/TCR/TCNI.
• Presione el botón "+" / "-" para establecer y guardar los parámetros y mantener la configuración.

Modo	Rango de ajuste	Operación y ajuste de valores
WATT	1-160W (Predeterminado: 5W)	Presione el botón "+" / "-" para entrar en el modo de ajuste, presione el botón "+" / "-" durante mucho tiempo para ajustar rápidamente.
VOLTAGE	0.5-8V (Predeterminado: 4.85V)	Presione el botón "+" / "-" para entrar en el modo de ajuste, presione el botón "+" / "-" durante mucho tiempo para ajustar rápidamente.
BYPASS	Voltaje máximo 8.5V, potencia máxima 160W	Presione el botón "+" / "-" para entrar en el modo de ajuste, presione el botón "+" / "-" durante mucho tiempo para ajustar rápidamente.
CPS	1-160W (Predeterminado: 100W)	Presione el botón "+" / "-" para entrar en el modo de ajuste, presione el botón "+" / "-" durante mucho tiempo para ajustar rápidamente.
TC	200-600°F (Predeterminado: 350°F)	Presione el botón "+" / "-" para entrar en el modo de ajuste, presione el botón "+" / "-" durante mucho tiempo para ajustar rápidamente.

Nota:
1. El dispositivo muestra "NEW ATOMIZER" con bajo ajuste de TC (10~15W) antes de que el vapeo actual se active, el valor predeterminado de 350°F se restaurará después de 3 segundos y se actualizará la potencia de vapeo actual. Si presiona el botón "+" durante mucho tiempo, el valor de la última vez se mostrará.

Información de la resistencia:

Llenado del tanque: